



### Model No. : HM2016 / Flow Controller

- Display: 16 channels x 4 line LCD, flow rate (LPM, m3/h)
- Ramp: Auto check overrun
- Input frequency: 0 to 1 KHz
- Input: 4-20mA, pulse
- Power: AC90V to 250V
- Pulse output: 1cc, 10cc, 100cc, 1L, 10L, 100L, 1000L
- Size: 144 x 72 x 134 mm

### Model No. : HM2011 / Flow Controller

- Display: 16 channels x 4 line LCD, flow rate (LPM, m3/h)
  - Ramp: Auto check overrun
  - Input frequency: 0 to 1 KHz
    - Output: 4-20mA, pulse
    - Power: AC90V to 250V
- Pulse output: 1cc, 10cc, 100cc, 1L, 10L, 100L, 1000L
  - Size: 144 x 72 x 131 mm



### Model No. : DY-BT8 / Batch Counter

- Display: 7 compartments
- Power: AC 90V ~ 250V
- Scale range: 0.00001 ~ 999.00000
- Measure range: 99,999,999 ~ 99,999,99
- Output : Pulse, two SPDT Relays
- Size: 144 x 72 x 129 mm

### Model No. : DYB-6 / Controller

- AC power: AC90 ~ 250V (about 10VA)
  - Counting speed: 30HZ, 2000HZ
  - Input method: contact OR NPN, PNP
- Control output: RELAY STDT 1C (DC30V/100MA)
  - Ambient temperature: -10 ~ 55°C
  - storage temperature: -25 ~ 65 ° c
  - Ambient humidity: 35 to 85%RH
  - Size: 71 x 71 x 112 mm



### Model No. : DY-T8 / Total Counter

- Power supply voltage: AC90 - 240V
- Input method: using PNP
- SCALE range: 0.00001 to 999.0000
- Measurement range: 99999999-999999.999 (8DIGIT COUNTER)
- DISPLAY method: 7-Segment
- Input speed: 2KCPS/30CPS selection
- Size: 72 x 36 x 96 mm